



Progress of plasma table-top X-ray lasers at LLNL

**Yuelin Li¹, James Dunn², Albert Osterheld²,
Joseph Nilsen², and Vyacheslav N. Shlyaptsev³**

*¹Institute of Laser Science and Applications
Lawrence Livermore National Laboratory, P.O. Box 808, Livermore, CA 94550*

²Lawrence Livermore National Laboratory, P.O. Box 808, Livermore, CA 94550

*³Department of Applied Science
University of California at Davis-Livermore, Livermore, CA 94550*

Work performed under the auspices of the US Department of Energy by the Lawrence Livermore National Laboratory under Contract No. W-7405-Eng-48



Institute for Laser Science and Applications


Free Electron Laser Conference 2000, 13 to 18 August 2000, Durham, North Carolina

7/21/2000



What is a plasma X-ray laser

Plasma lasers are traditional lasers that lase via population inversion on atomic and ionic energy levels




Population inversion: Ni-like X-ray lasers




Ni-like Mo (Z=42) (Mo^{14+})


Ground state: $1s^2 2s^2 2p^6 3s^2 3p^6 3d^{10}$



Wavelengths of Ni-like lasers




X-ray laser at LLNL: NOVA experiments (1980s-early 1990s)



- Lasing from 3.5 to 33 nm
- X-ray laser interferometer/More deflectometry
- X-ray laser microscopy/holography

Pump energies: ~kJ

Rep Rate: ~hours




Institute for Laser Science and Applications

Free Electron Laser Conference 2000, 13 to 18 August 2000, Durham, North Carolina

7/21/2000



The transient collisional excitation scheme



**The long pulse prepares a large plasma
The short pulse generates the high gain**


- The high gain allows efficient amplification (saturation) with a short target length
- Using the compact CPA lasers

Notes:


$$\text{Plasma X-ray laser gain} = (\text{FEL gain length})^{-1}$$

$$\text{Plasma X-ray laser gain length} = \ln(\text{FEL gain})$$

RADEX: Max. Temperatures (Ni-like Pd, Z=46)



RADEX: Max. Gain (Ni-like Pd, Z=46)



Nickles et al, Phys Rev Lett 78, 2748 (1997); Dunn et al, Phys Rev Lett 80, 2825 (1998)


Free Electron Laser Conference 2000, 13 to 18 August 2000, Durham, North Carolina

7/21/2000




Institute for Laser Science and Applications

LLNL Table-Top X-ray Laser Facility — COMET





COMET Laser Parameters

Long Pulse	15 J, 600 ps
Short Pulse	7.5 J, 0.5 ps
Probe 2 ω , 3 ω	0.5 ps
Beam 3	1 J, 0.5 ps 4 J, 600 ps



Detailed setup: traveling wave (TWE) and diagnostics



Institute for Laser Science and Applications




Free Electron Laser Conference 2000, 13 to 18 August 2000, Durham, North Carolina

7/21/2000

X-ray laser diagnostics: multilayer imaging system




Multilayer mirror reflectivity




On-axis X-ray laser (XRL) spectra



XRL lines



Spectra of Pd and Mo



Institute for Laser Science and Applications


Free Electron Laser Conference 2000, 13 to 18 August 2000, Durham, North Carolina

7/21/2000


Saturation of the 18.9 nm Ni-like Mo X-ray laser



Spectrum of a 1 cm target



A gain length of **16.6** is obtained



Institute for Laser Science and Applications

Li et al, submitted to *Science*



Free Electron Laser Conference 2000, 13 to 18 August 2000, Durham, North Carolina

7/21/2000

XRL divergence





Measurement of the Ni-like Mo 18.9 nm XRL beam divergence



Temporal characterization of Ni-like Mo XRL at 18.9 nm



When no traveling wave is applied, the X-ray experiences the gain as a function the propagation distance, i.e., the traveling time




Dunn et al, Opt Lett 24, 101 (1999)

Free Electron Laser Conference 2000, 13 to 18 August 2000, Durham, North Carolina


7/21/2000



A gain length of 21.6 is obtained



A gain life time of ~4 ps is deduced from the non-traveling wave measurement





Dunn et al, submitted to *Phys Rev Lett*

Free Electron Laser Conference 2000, 13 to 18 August 2000, Durham, North Carolina

7/21/2000


Mo 18.9 nm XRL output energy and intensity






Stability of the Plasma XRL

Comparison of near-field images



$E_L = 1-1.5 \text{ J}$, $E_s = 5 \text{ J}$, $\Delta t = 0.7 \text{ ns}$, targets are 1 cm long.

XRL output of a set of non-consecutive shots



Institute for Laser Science and Applications


Free Electron Laser Conference 2000, 13 to 18 August 2000, Durham, North Carolina

7/21/2000




Brightness of the Plasma XRL

Peak Brightness



Average Brightness




Institute for Laser Science and Applications

Free Electron Laser Conference 2000, 13 to 18 August 2000, Durham, North Carolina

7/21/2000



Future work



Institute for Laser Science and Applications

Free Electron Laser Conference 2000, 13 to 18 August 2000, Durham, North Carolina

7/21/2000



Summary of LLNL XRL accomplishments

Summary

Demonstration of X-ray lasers at wavelengths from 12 to 33 nm, the first saturated table top XRL system at wavelengths below 20 nm, characterization of the XRL output and demonstration of control of the XRL output

This research has laid the foundation of further development of a user facility for application in plasma diagnostics, surface physics, and imaging experiments, as well as a seeding source for X-ray FEL

Plasma XRL will complement the third and the fourth generation light sources with comparable brightness but better compactness.



Institute for Laser Science and Applications

Free Electron Laser Conference 2000, 13 to 18 August 2000, Durham, North Carolina

7/21/2000